



ސަވަދީ ޖަހާލުމުގެ ސަރުކާރު

10 ވަނަ ދުވަހުގެ ސަވަދީ ޖަހާލުމުގެ ސަރުކާރު	ދިވެހިރާއްޖޭގެ ސަރުކާރު:
38/2025/G-012	ދިވެހިރާއްޖޭގެ ސަރުކާރު:
(IUL)38-AB/38/2025/205	ދިވެހިރާއްޖޭގެ ސަރުކާރު:
20 ޖަނުއަރީ 2025	ދިވެހިރާއްޖޭގެ ސަރުކާރު:

ދިވެހިރާއްޖޭގެ ސަރުކާރުގެ ނަންބަރު:	
ދިވެހިރާއްޖޭގެ ސަރުކާރުގެ ނަންބަރު 5 ވަނަ ދުވަހުގެ ސަވަދީ ޖަހާލުމުގެ ސަރުކާރު، ރާއްޖޭގެ ސަރުކާރު، ދިވެހިރާއްޖޭގެ ސަރުކާރު.	ދިވެހިރާއްޖޭގެ ސަރުކާރު:
29 ޖަނުއަރީ 2025	ދިވެހިރާއްޖޭގެ ސަރުކާރު:
11:30	މިއަދު:

ދިވެހިރާއްޖޭގެ ސަރުކާރުގެ ނަންބަރު ދިވެހިރާއްޖޭގެ ސަރުކާރުގެ ނަންބަރު

[illegible]

2.1.2 $\frac{1}{2} \frac{d}{dt} \left(\frac{1}{2} m v^2 \right) = \frac{1}{2} m v \frac{dv}{dt} = \frac{1}{2} m v \frac{d}{dt} \left(\frac{1}{m} \frac{d}{dt} \right) = \frac{1}{2} \frac{d}{dt} \left(\frac{1}{2} m v^2 \right)$

2.1.4 رَدِّ رُوخُ قُتُقُتُرُسُ وَاوُتُقُيُيُ قُتُقُتُرُسُ قُتُقُتُرُسُ قُتُقُتُرُسُ قُتُقُتُرُسُ رَدِّ رُوخُ وَاوُتُقُيُيُ قُتُقُتُرُسُ

[illegible][illegible][illegible]

4.2 $\frac{d}{dt} \left(\frac{1}{2} m v^2 \right) = \frac{d}{dt} \left(\frac{1}{2} m \dot{x}^2 \right) = m \dot{x} \ddot{x} = m \dot{x} a = \dot{x} F = \frac{d}{dt} (x F) - x \frac{dF}{dt}$

Page 3 of 8

[illegible]

سُورَةُ ١- (وَجِبْ مَعَكُمْ) مَعَكُمْ

SPECIFICATIONS FOR MIC	
Item	Headset Cardioid Condenser Microphone with Windscreen
Quantity	10
Working Range	Minimum 100 m
Audio Frequency Response	Minimum 50 Hz – 15 KHz
Signal to Noise	>90 dB
Tone Key Frequency	35 kHz
Transmitter	Belt pack Transmitter
Input Connector	XLR
Input Impedance	1M Ω
Input Gain range	Minimum 38 dB
Battery Life	Minimum 8 hours
Receiver:	Wireless Receiver
Audio Output Level- Unbalanced	Minimum +14 dBu
Audio Output level - Balanced	Minimum +9 dBu
Frequency Scan	Automatic
Out Put	Balanced XLR & Unbalanced 1/4 " outputs
Sensitivity	-100 dBm / 30 dB sinad
Power	DC Adaptor

- [illegible]